

1000V INSULATED SOCKETS



3/8" Drive Hex Head Sockets SAE - Standard Length

Hex Size	Part No.	Overall Length, in.	Bit Length, in.
1/8"	TW4-I	2.25	1.5
5/32"	TW5-I	2.25	1.5
3/16"	TW6-I	2.25	1.5
7/32"	TW7-I	2.25	1.5
1/4"	TW8-I	2.25	1.5
5/16"	TW10-I	2.25	1.5
3/8"	TW12-I	2.25	1.5

Individually insulated and tested to ASTM F1505 Standards. ⚠



3/8" Drive Hex Head Sockets SAE - Long Length

Hex Size	Part No.	Overall Length, in.	Bit Length, in.
1/8"	TW4L-I	4.00	3.0
5/32"	TW5L-I	4.00	3.0
3/16"	TW6L-I	4.00	3.0
7/32"	TW7L-I	4.00	3.0
1/4"	TW8L-I	4.00	3.0
5/16"	TW10L-I	4.00	3.0
3/8"	TW12L-I	4.00	3.0

Individually insulated and tested to ASTM F1505 Standards. ⚠



3/8" Drive Hex Head Sockets Metric - Standard Length

Hex Size	Part No.	Overall Length, mm	Bit Length, mm
4mm	MTW4-I	57	31
5mm	MTW5-I	57	31
6mm	MTW6-I	57	31
7mm	MTW7-I	57	31
8mm	MTW8-I	57	31
9mm	MTW9-I	57	31
10mm	MTW10-I	57	31

Individually insulated and tested to ASTM F1505 Standards. ⚠

⚡ Important: An insulated extension is always required between the ratchet and the socket.